



# PHILLIPS INSERT BITS



ACR®  
STYLE

| HEX DRIVE | LENGTH | POINT SIZE | DOMESTIC |         | IMPORTED |            | SPECIAL NOTES        |  |
|-----------|--------|------------|----------|---------|----------|------------|----------------------|--|
|           |        |            | EVCO #   | PRICE   | EVCO #   | PRICE      |                      |  |
| 1/4       | 1      | 0          | 4P0A     |         | 4P0      |            |                      |  |
|           |        | 1          | 4P1A     |         | 4P1      |            |                      |  |
|           |        | 2          | 4P2A     |         | 4Q2      |            | QUADREX              |  |
|           |        | 3          | 4P3A     |         | 4P2      |            |                      |  |
|           |        | 4          |          |         | 4P3      |            |                      |  |
|           | 1 1/2  | 2          |          |         | 4P4      |            |                      |  |
|           | 2      | 2          |          |         | 001P2    |            |                      |  |
|           | 1      | 1          |          |         | 002P2    |            |                      |  |
|           |        | 2          | 4PR2A    |         | 4PR1     |            | REDUCED              |  |
|           | 5/16   | 1 1/4      | 2        |         | 4PR2     |            | REDUCED              |  |
| 3         |        |            |          | 600P2   |          |            |                      |  |
| 4         |        |            |          | 600P3   |          |            |                      |  |
|           |        |            |          | 600P4   |          |            |                      |  |
| 1/4       | 1      | 1          |          | 4P1M    |          | MILLED CUT |                      |  |
|           |        | 2          |          | 4P2M    |          | MILLED CUT |                      |  |
|           |        | 3          |          | 4P3M    |          | MILLED CUT |                      |  |
|           | 1      | 1          | 4        |         | 4P2L     |            | DEPTH SETTER         |  |
|           |        |            | 1        | 4P1ACR  |          |            | ACR® STYLE           |  |
|           |        |            | 2        | 4P2ACR  |          |            | ACR® STYLE           |  |
|           |        |            | 3        | 4P3ACR  |          |            | ACR® STYLE           |  |
|           |        |            | 2        | 4PR2ACR |          |            | ACR® STYLE (REDUCED) |  |
|           |        |            |          |         |          |            |                      |  |
|           |        |            |          |         |          |            |                      |  |



QUADREX



4P2L

The Interlocking Ribs of the ACR® Anti-Cam Provide Higher Torque  
ACR® Bits are Interchangeable with Standard Phillips Components

# PHILLIPS POWER BITS



| HEX DRIVE | LENGTH | POINT SIZE | DOMESTIC |       | IMPORTED |       | SPECIAL NOTES |  |
|-----------|--------|------------|----------|-------|----------|-------|---------------|--|
|           |        |            | EVCO #   | PRICE | EVCO #   | PRICE |               |  |
| 1/4       | 1 1/16 | 1          | 42P1A    |       | 42P1     |       |               |  |
|           |        | 2          | 42P2A    |       | 42P2     |       |               |  |
|           |        | 2          |          |       | 42Q2     |       | QUADREX       |  |
|           |        | 3          | 42P3A    |       | 42P3     |       |               |  |
|           | 2 1/4  | 2 3/4      | 1        | 43P1A |          | 43P1  |               |  |
|           |        |            | 2        | 43P2A |          | 43P2  |               |  |
|           |        |            | 3        | 43P3A |          | 43P3  |               |  |
|           | 3 1/2  | 3 1/2      | 1        | 44P1A |          | 44P1  |               |  |
|           |        |            | 2        | 44P2A |          | 44P2  |               |  |
|           |        |            | 3        | 44P3A |          | 44P3  |               |  |
|           | 6      | 6          | 1        |       |          | 46P1  |               |  |
|           |        |            | 2        | 46P2A |          | 46P2  |               |  |
| 3         |        |            |          |       | 46Q2     |       | QUADREX       |  |
| 3/16      | 3 1/2  | 2          | 430P2    |       | 46P3     |       |               |  |
|           |        | 3          | 430P3    |       |          |       |               |  |
| 1/4       | 1 1/16 | 1          | 42P1ACR  |       |          |       | ACR® STYLE    |  |
|           |        | 2          | 42P2ACR  |       |          |       | ACR® STYLE    |  |
|           |        | 3          | 42P3ACR  |       |          |       | ACR® STYLE    |  |

The Interlocking Ribs of the ACR® Anti-Cam Provide Higher Torque  
ACR® Bits are Interchangeable with Standard Phillips Components

ACR® IS A REGISTERED TRADEMARK OF PHILLIPS SCREW COMPANY

evco

MANY SCREWDRIVING ACCESSORIES CAN BE SKIN CARDED - 10 PER CARD - ADD 10C TO THE PART NO.